

FURUTECH

IEC Connector

<p>FI-33(R) 5,270.-/pcs.</p> <p>FI-33(G) 4,280.-/pcs.</p>	<p>High End Performance 20A IEC Inlet</p> <ul style="list-style-type: none"> • Pure copper α (Alpha) Conductor • Material: Nylon/fiberglass • Specified for wire diameters of 4mm (set screw) • Dimensions: 60.4mm (W) x 30.4mm (D) x 38.7mm (H) • Rated: 20A/125V and 16A/250V 	
<p>FI-09(R) 4,610.-/pcs.</p> <p>FI-09(G) 3,620.-/pcs.</p>	<p>High End Performance IEC Inlet</p> <p>Pure copper α (Alpha) Conductor</p> <ul style="list-style-type: none"> •Materials: Nylon/fiberglass •Specifications: Accommodates wire diameters to 4mm (set-screw) •Dimensions: 60 (W) x 30mm (D) x 36.2mm (H) •Body length 40.0mm x 44mm diameter x 80mm overall length •Rated: 15A/250V 	 <p>FI-09 (R)</p>
<p>AC-INLET (R) 830.-/pcs.</p> <p>AC-INLET(G) 610.-/pcs</p>	<p>High Performance IEC Inlet</p> <ul style="list-style-type: none"> • α (Alpha) copper alloy conductor • PBT and fiberglass housing • Dimensions: 44.0mm (W) x 28.6mm (D) x 33.0mm (H) • Rating: 10A/250V • Standard : IEC 320-1 C14 • Approvals : UL/CSA/VDE/DEMKO/SEMKO/NEMKO/FIMKO 	
<p>FI-03(R) 1,260.-/pcs.</p> <p>FI-03(G) 980.-/pcs.</p>	<p>High Performance IEC Inlet</p> <ul style="list-style-type: none"> • α (Alpha) Eutectic (low temperature) cast copper alloy Conductor • PBT and fiberglass housing • Connections: Soldered • Dimensions: 50.9mm (W) x 24.1mm (D) x 28.8 (H) • Rated: 15A/125V 10A/250V 	
<p>FI-06(R) 1,400.-/pcs.</p> <p>FI-06(G) 1,200.-/pcs.</p>	<p>FI-06(G) & FI-06(R) Gold or Rhodium plated α (Alpha) Conductors milled from solid Pure Copper Rated: 15A/250V</p> <ul style="list-style-type: none"> • Materials: Nylon/fiberglass • Specifications: Accommodates wire diameters up to 3.5mm (set-screw) • Dimensions: 50.5 (W) x 23.9mm (D) x 33.5mm (H) \pm0.1mm 	
<p>AC-1001(G) 2,200.-/pcs.</p> <p>AC-1501(R) 3,580.-/pcs.</p>	<p>High End Performance EMI Filter AC 1001 & AC 1501 Inlet series:</p> <p>Rhodium plated or 24k gold plated α (Alpha) non magnetic copper alloy conductors</p> <p>Outer cover Cr Plated steel plate</p> <p>Inner cover Nylon glass fiber</p> <p>Inner Box Nylon glass fiber</p> <p>Inner parts held by Piezo Epoxy</p> <p>AC 1001 Rating:115V/250V 10A 50/60Hz</p> <p>AC 1501 Rating:115V/250V 15A 50/60Hz</p>	

FURUTECH

IEC Connector

NEW

FI-06 NCF(R)
2,000-/pcs.

Furutech's Ultimate IEC Inlet Series

- α (Alpha) Pure-Copper Rhodium-plated Conductor
- Materials: Nylon/fiberglass with special "NCF" anti-resonance damping material - nano-sized crystalline, piezo ceramic particles and carbon powder
- Specifications: Accommodates wire diameters up to 3.5mm (set-screw)
- Dimensions: 50.5 (W) x 23.9mm (D) x 33.5mm (H) ± 0.1 mm
- Rated: 15A/250V

