

# FURUTECH

## BANANA & SPADE

<p><b>CF-201(R)</b> <b>(2 pcs./set)</b></p> <p><b>8,270.-/set</b></p>	<p>CF-201(R) Pure Transmission Spade Connector</p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) pure-copper rhodium-plated center conductor</li> <li>• <math>\alpha</math> (Alpha) nonmagnetic stainless steel body</li> <li>• Carbon fiber and nonmagnetic stainless steel housing</li> <li>• Conductors fixed by set screw or solder</li> <li>• Specially designed copper alloy set screw ensures stability</li> <li>• Specified for wire diameters max. 5.5mm</li> <li>• Dimensions: 15.2mm diameter x 70.0mm overall length</li> </ul>	
<p><b>CF-202(R)</b> <b>(2 pcs./set)</b></p> <p><b>11,000.-/set</b></p>	<p>Carbon Fiber Series Banana Connector CF-202(R)</p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) pure-copper rhodium-plated center conductor</li> <li>• <math>\alpha</math> (Alpha) nonmagnetic stainless steel body</li> <li>• Beautifully finished highly damped carbon fiber and nonmagnetic stainless steel housing</li> <li>• Conductor wire fixed with set screw or solder</li> <li>• Specially designed wire compression clamp enhances stability and contact area</li> <li>• Strain relief/resonance dampening ring</li> <li>• Locking compression collar for small diameter wire</li> <li>• Specified for wire diameters to max. 5.5mm</li> <li>• Dimensions: 15.2mm diameter x 64.2mm overall length</li> </ul>	
<p><b>FP-201(R)</b> <b>(4 pcs./set)</b></p> <p><b>4,550.-/set</b></p> <p><b>FP-201(G)</b> <b>(4 pcs./set)</b></p> <p><b>3,410.-/set</b></p>	<p>High Performance Audio Spade Terminals</p> <ul style="list-style-type: none"> <li>• Pure copper <math>\alpha</math> (Alpha) Conductors</li> <li>• Connections: Set screw or soldered</li> <li>• Specified for cable diameters up to 6mm</li> <li>• Dimensions: Space between Conductor: 8.2mm o 12.9mm <math>\pm</math> 0.1 (W) x 40mm <math>\pm</math> 0.1mm overall length</li> </ul>	 
<p><b>FP-203(R)</b> <b>(4 pcs./set)</b></p> <p><b>2,500.-/set</b></p> <p><b>FP-203(G)</b> <b>(4 pcs./set)</b></p> <p><b>2,120.-/set</b></p>	<p>High Performance Audio Spade Terminals</p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) Pure copper Conductors</li> <li>• Connections : Soldered or Press</li> <li>• Specified for cable diameters up to 4mm</li> <li>• Dimensions: Space between Conductor: 8.2mm o 12.9mm <math>\pm</math> 0.1 (W) x 24mm <math>\pm</math> 0.1mm overall length</li> </ul>	 


# FURUTECH

## BANANA & SPADE

<p><b>FP-202(R)</b> (4 pcs./set) <b>5,300.-/set</b></p> <p><b>FP-202(G)</b> (4 pcs./set) <b>4,400.-/set</b></p>	<p>High Performance Audio Banana Connectors</p> <ul style="list-style-type: none"> <li>• Eutectic cast copper alloy <math>\alpha</math> (Alpha) pins</li> <li>• Connections: Set-screw</li> <li>• Specified for cable diameters up to 7mm</li> <li>• Dimensions: Space between Conductor: 8.2mm o 12mm diameter x 26.7mm <math>\pm</math> 0.1mm (H) x 46mm overall length</li> </ul>	
<p><b>FP-200B(R)</b> (4 pcs./set) <b>4,550.-/set</b></p> <p><b>FP-200B(G)</b> (4 pcs./set) <b>3,510.-/set</b> <b>830.-/pcs.</b></p>	<p>High Performance Audio Banana Connectors</p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) Phosphor Bronze pin</li> <li>• Connections: Set-screw or Soldered</li> <li>* Contact pin specially designed to increase contact area and effect stable more transmission.</li> <li>* Unique main body design that ensures very firm wire connections that can be fixed by set screw or soldered.</li> <li>* Treated with FURUTECH <math>\alpha</math>(Alpha) Process to minimize transmission loss</li> <li>* Material: Banana Conductor—Phosphor Bronze Plate / Housing—Copper alloy</li> <li>* Specifications: Max. Wire diameters up to <math>\phi</math>5.0mm</li> <li>* Dimensions: Housing---<math>\phi</math>11.1mm X 30.3 mm L, Banana Conductor---<math>\phi</math>4.6mm X 19.7 mm L, Overall length : 50 mm</li> </ul>	
<p><b>FP-209-10(G)</b> (20pcs./set)</p> <p><b>3,030-/set</b> <b>152.-/pcs.</b></p>	<p>High Performance RCA connector series FP-209-10(G)</p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) Pure copper Conductors</li> <li>• Connections: solder or crimp</li> <li>• Specified for wire diameters up to 4mm (8AWG)</li> <li>• Dimensions: 8mm <math>\pm</math> 0.1mm (W) x 25mm <math>\pm</math> 0.1mm overall length</li> <li>• Perfect for use with Furutech wall receptacle connections and Furutech AC / IEC power connections</li> </ul>	
<p><b>FP-209-10(G)</b> (10pcs./set)</p> <p><b>1,680-/set</b> <b>168.-/pcs.</b></p>	<ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) Pure copper plate (t:1.0mm)</li> <li>• Connections: solder or crimp</li> <li>• Specified for wire diameters up to 10AWG</li> <li>• Dimensions: Outside 8mm, Inside 4.3 mm 0.1mm(W)x 25mm 0.1mm overall length.</li> <li>• Perfect for use with Furutech wall receptacle connections and Furutech AC / IEC power connections</li> <li>• 10pcs per set</li> </ul>	

# FURUTECH

## BANANA & SPADE

<p><b>FT-212(G)</b> <b>(4 pcs./set)</b> <b>6,460.-/set</b></p> <p><b>FT-212(R)</b> <b>(4 pcs./set)</b> <b>7,380.-/set</b></p>	<p>High End Performance Banana Connector</p> <p>Main conductor : 24k gold-plated <math>\alpha</math> (Alpha) Pure copper conductor Housing : Black Polycarbonate finished Insulation Body: Nylon/fiberglass with piezo ceramic resin Termination: set screw</p> <p>Specified for core diameters up to 4.2mm Specified for core insulation diameters up to 7.4mm Dimensions : Housing : 18.0 x <math>\varnothing</math> 16.0 x20.0mm (H) Overall height/ Total overall length: 54.3mm appox. FT-212(R) –Rhodium-Plated version by request</p>	
<p><b>FT-211(G)</b> <b>(4 pcs./set)</b> <b>5,670.-/set</b></p> <p><b>FT-211(R)</b> <b>(4 pcs./set)</b> <b>6,580.-/set</b></p>	<p>High End Performance Spade Connector</p> <p>Main conductor : 24k gold-plated <math>\alpha</math> (Alpha) Pure copper conductor Housing : Black Polycarbonate finished Insulation Body: Nylon/fiberglass with piezo ceramic resin Termination: set screw</p> <p>Specified for core diameters up to 4.2mm Specified for core insulation diameters up to 7.4mm Dimensions : Housing : 18.0 x <math>\varnothing</math> 16.0 x20.0mm (H) Overall height/ Total overall length: 56.2mm appox. FT-211(R) –Rhodium-Plated version by request</p>	