




FURUTECH

BANANA & SPADE

<p>CF-201-N1(R) (2 pcs./set)</p> <p>13,200.-/set</p>	<p>CF-201(R) Pure Transmission Spade Connector</p> <ul style="list-style-type: none"> • α (Alpha) pure-copper rhodium-plated center conductor • α (Alpha) nonmagnetic stainless steel body • Carbon fiber and nonmagnetic stainless steel housing • Conductors fixed by set screw or solder • Specially designed copper alloy set screw ensures stability • Specified for wire diameters max. 5.5mm • Dimensions: 15.2mm diameter x 70.0mm overall length 	
<p>CF-202-N1(R) (2 pcs./set)</p> <p>15,200.-/set</p>	<p>Carbon Fiber Series Banana Connector CF-202(R)</p> <ul style="list-style-type: none"> • α (Alpha) pure-copper rhodium-plated center conductor • α (Alpha) nonmagnetic stainless steel body • Beautifully finished highly damped carbon fiber and nonmagnetic stainless steel housing • Conductor wire fixed with set screw or solder • Specially designed wire compression clamp enhances stability and contact area • Strain relief/resonance dampening ring • Locking compression collar for small diameter wire • Specified for wire diameters to max. 5.5mm • Dimensions: 15.2mm diameter x 64.2mm overall length 	
<p>FP-201(R) (4 pcs./set)</p> <p>6,400.-/set</p> <p>FP-201(G) (4 pcs./set)</p> <p>5,700.-/set</p>	<p>High Performance Audio Spade Terminals)</p> <ul style="list-style-type: none"> • Pure copper α (Alpha) Conductors • Connections: Set screw or soldered • Specified for cable diameters up to 6mm • Dimensions: Space between Conductor: 8.2mm o 12.9mm \pm 0.1 (W) x 40mm \pm 0.1mm overall length 	
<p>FP-203(R) (4 pcs./set)</p> <p>3,200.-/set</p> <p>FP-203(G) (4 pcs./set)</p> <p>2,900.-/set</p>	<p>High Performance Audio Spade Terminals</p> <ul style="list-style-type: none"> • α (Alpha) Pure copper Conductors • Connections : Soldered or Press • Specified for cable diameters up to 4mm • Dimensions: Space between Conductor: 8.2mm o 12.9mm \pm 0.1 (W) x 24mm \pm 0.1mm overall length 	

FURUTECH

BANANA & SPADE

<p>FP-202(R) (4 pcs./set) 7,600.-/set</p> <p>FP-202(G) (4 pcs./set) 6,700.-/set</p>	<p>High Performance Audio Banana Connectors</p> <ul style="list-style-type: none"> • Eutectic cast copper alloy α (Alpha) pins • Connections: Set-screw • Specified for cable diameters up to 7mm • Dimensions: Space between Conductor: 8.2mm o 12mm diameter x 26.7mm \pm 0.1mm (H) x 46mm overall length 	
<p>FP-200B(R) (4 pcs./set) 6,000.-/set</p> <p>FP-200B(G) (4 pcs./set) 5,500.-/set</p>	<p>High Performance Audio Banana Connectors</p> <ul style="list-style-type: none"> • α (Alpha) Phosphor Bronze pin • Connections: Set-screw or Soldered * Contact pin specially designed to increase contact area and effect stable more transmission. * Unique main body design that ensures very firm wire connections that can be fixed by set screw or soldered. * Treated with FURUTECH α(Alpha) Process to minimize transmission loss * Material: Banana Conductor—Phosphor Bronze Plate / Housing—Copper alloy * Specifications: Max. Wire diameters up to ϕ5.0mm * Dimensions: Housing---ϕ11.1mm X 30.3 mm L, Banana Conductor---ϕ4.6mm X 19.7 mm L, Overall length : 50 mm 	
<p>FP-209-10(G) (20pcs./set) 205.-/pcs.</p>	<p>High Performance RCA connector series FP-209-10(G)</p> <ul style="list-style-type: none"> • α (Alpha) Pure copper Conductors • Connections: solder or crimp • Specified for wire diameters up to 4mm (8AWG) • Dimensions: 8mm \pm 0.1mm (W) x 25mm \pm 0.1mm overall length • Perfect for use with Furutech wall receptacle connections and Furutech AC / IEC power connections 	
<p>FP-209-10(R) (10pcs./set) 230.-/pcs.</p>	<ul style="list-style-type: none"> • α (Alpha) Pure copper plate (t:1.0mm) • Connections: solder or crimp • Specified for wire diameters up to 10AWG • Dimensions: Outside 8mm, Inside 4.3 mm 0.1mm(W)x 25mm 0.1mm overall length. • Perfect for use with Furutech wall receptacle connections and Furutech AC / IEC power connections • 10pcs per set 	

FURUTECH

BANANA & SPADE

<p>FT-212(G) (4 pcs./set) 9,700.-/set</p> <p>FT-212(R) (4 pcs./set) 10,800.-/set</p>	<p>High End Performance Banana Connector</p> <p>Main conductor : 24k gold-plated α (Alpha) Pure copper conductor Housing : Black Polycarbonate finished Insulation Body: Nylon/fiberglass with piezo ceramic resin Termination: set screw Specified for core diameters up to 4.2mm Specified for core insulation diameters up to 7.4mm Dimensions : Housing : 18.0 x \varnothing 16.0 x20.0mm (H) Overall height/ Total overall length: 54.3mm approx. FT-212(R) –Rhodium-Plated version by request</p>	
<p>FT-211(G) (4 pcs./set) 8,300.-/set</p> <p>FT-211(R) (4 pcs./set) 9,250.-/set</p>	<p>High End Performance Spade Connector</p> <p>Main conductor : 24k gold-plated α (Alpha) Pure copper conductor Housing : Black Polycarbonate finished Insulation Body: Nylon/fiberglass with piezo ceramic resin Termination: set screw Specified for core diameters up to 4.2mm Specified for core insulation diameters up to 7.4mm Dimensions : Housing : 18.0 x \varnothing 16.0 x20.0mm (H) Overall height/ Total overall length: 56.2mm approx. FT-211(R) –Rhodium-Plated version by request</p>	
<p>CF-202 NCF(R) 16,500.-/set</p>	<p>High End Performance Banana connector (Carbon fiber finish)2pcs/set</p> <p>Specifications</p> <ul style="list-style-type: none"> Specified for wire diameters max. 5.5mm Dimensions: 15.2mm diameter x 60.5mm overall length approx. Net Weight: 33.4 g approx. <p>Accessories</p> <ul style="list-style-type: none"> 2mm hex head screwdriver (H 2.0)*1 PC Hex socket set screws (M4 x4)*2pcs/Set 	
<p>CF-201 NCF(R) 14,500.-/set</p>	<p>High End Performance Spade connector (Carbon fiber finish)2pcs/set</p> <p>Specifications</p> <ul style="list-style-type: none"> Specified for wire diameters max. 5.5mm Dimensions: 15.2mm diameter x 60.5mm overall length approx. Net Weight: 33.4 g approx. <p>Accessories</p> <ul style="list-style-type: none"> 2mm hex head screwdriver (H 2.0)*1 PC Hex socket set screws (M4 x4)*2pcs/Set 	