




# FURUTECH

## FUSE & EXCEPTIONALS

<p><b>Fuse TF-series</b></p> <p><b>20mm 3,100.-</b>  <b>0.5A,1A,2A,3.15A,4A</b>  <b>5A,6.3A,8A,10A,15A</b></p> <p><b>32mm 3,500.-</b>  <b>1A,2A,3.15A,4A,</b>  <b>5A,6.3A, 8A,10A,15A</b></p>	<p>Furutech Select Series Pure Transmission Fuses          20mm and 32mm Nonmagnetic Time-lag Fuses          Material: Copper Caps with direct rhodium plating.          Conductor: Special low induction copper alloy</p> <p>Audio connoisseurs know that all links in the signal path are as important as the next. Furutech engineers solutions that optimize every pathway and junction; any unaccounted for characteristic weakness (i.e., contact resistance, EMI-radiating junctions, RFI) diminishes performance as noise and distortion builds. Using the best materials and processes available along with meticulous attention to build quality is a large part of the Pure Transmission engineering equation: The fuse is equipped with rhodium-plated OFC copper caps and a special low-inductance copper alloy conductor, ceramic body with special damping filler. All metal parts treated with Furutech's patented Alpha Super Cryogenic and Demagnetizing process. These beautifully made audiophile fuses are engineered to withstand 1 nanosecond at a full 1500 watts, and rated at 125mA/6.3A.</p>	
<p><b>GS Series</b>  <b>Crimp Sleeves</b></p> <p><b>3,790.-</b></p>	<p>High Performance Crimp Sleeves          * 24k Gold plated non-magnetism <math>\alpha</math>- Conductor          * Material: Pure Copper Pipe</p> <p>GS-11P (I.D. :1.1mm X Overall long:6mm) for 20 AWG          GS-21P (I.D. :2.1mm X Overall long:10mm) for 14 AWG          GS-28P (I.D. :2.8mm X Overall long:10mm) for 12 AWG          GS-35P (I.D. :3.5mm X Overall long:10mm) for 10 AWG          GS-46P (I.D. :4.6mm X Overall long:10mm) for 8 AWG          GS-83P (I.D. :8.3mm X Overall long:20mm) for 4 AWG          GS-90P (I.D. 9.0mm X Overall long:20mm L) for 2 AW</p>	
<p><b>CF-080</b></p> <p><b>4,830-/pcs.</b></p>	<p>CF-080 AC Power Connector Damping Ring Outer Dimensions          The Suppressor (CF-080 AC Connector Damping Ring)          Furutech is known the world over for a huge variety of top-quality OEM parts. Furutech delivers consistently superior results by following Pure Transmission principles; examine every link in the power and signal path and ultimately optimize each and every element. And that especially includes damping mechanical resonances from a variety of mechanical and electrical effects. In highly resolved audio systems EVERYTHING makes a difference. The Suppressor Ring is a substantially-built silver-colored carbon fiber over nonmagnetic stainless steel damper ring with three fixing screws. It accommodates all Furutech AC connectors except the FI-50 Piezo Ceramic series that was a Best of Innovations Award-winner for its built-in mechanical and Piezoelectric damping. If your Furutech power cores are not equipped with FI-50 AC connectors adding the Suppressor Ring is the next best thing for low distortion playback.</p> <p>Features and Materials</p> <ul style="list-style-type: none"> <li>• Body: CNC Lathe stainless steel</li> <li>• Outer Cover Finish: Silver-Color Carbon Fiber</li> <li>• Fixing Screws: 3 SUS screws 3 x 3mm</li> <li>• Dimensions: 44.5<math>\psi</math> x 37.0 <math>\pm</math>0.3mm (L)overall length approx.</li> </ul>	

# FURUTECH

## FUSE & EXCEPTIONALS

<p><b>PC-Alpha</b></p> <p><b>1,380.-</b></p>	<p>Disc Pure Cleaner Keeps CDs and DVDs clean and free of static charge</p> <p>PC-Apha Pure Cleaner is used in dealing with the blurs on software (data side), caused by oxidize membranes, so as to reproduce the dynamics of sound effects as what they were at the time of recording. PC-Alpha is applicable to DVD, VCD, CD, CD-R, and CD-RW.</p>	
<p><b>NANO Liquid</b></p> <p><b>7,900.-</b></p>	<p>High End Performance NANO Liquid Contact Enhancer</p> <p>1.A/V equipment: RCA PIN, Jacket, Cannon connector, speaker terminal, AC Power plug for Amp. CD/VCD/DVD/MD and TV. 2.Computer equipment: connecting terminal and terminal seat for Monitor, Key board, hard disk, modem and printer, AC power plug, sound card. 3.All types of electronic and electric products: battery connection point, AC power plug. 4.Can be used in power Tool, all kinds of motor brush, measurement, communication and medical equipment and instruments.</p>	
<p><b>SK-III</b></p> <p><b>8,100.-</b></p>	<p>Disk media ( C D • D V D • L P ) AV Projector lenses and Plasma/LCD Screen Electrostatic Brush New Revolutionary Electrostatic AV accessory brush for improving sound and picture quality Ultimate Performance • Ultimate Refinement • Ultimate Luxury</p>	
<p><b>DF-2</b></p> <p><b>163,300.-</b></p>	<p>DF-2 FLATTENS PRECIOUS BUT WARPED LPs Rating • • 115V±10% AC Line 2A fuse European model • 230V±10% AC Line 2A fuse Energy Consumption • • • 100W (max) 25W (Norm) Heating plate maximum temp. • • • 65°C Note: The following LPs should not be treated in the DF-2. • LPs weighing less than 110g • Light LPs that were manufactured between 1973-74 (Oil crisis) weights range from 100g to 115g. Size: 445mm/17" W x 117mm/20" H x 547mm/7" D • Weight: 11kg/20lbs approx. Safe Usage Environment: Humidity 20% - 90% (No condensation) Temperature: 5C/41F – 35C/95F</p>	
<p><b>S-070</b> <b>(1 reel/10m.)</b></p> <p><b>2,380.-</b></p>	<p>High Performance Solder 4% fine silver content</p> <p>Betterment type solder Alloy: Silver 4%+ Tin 96% Ersin/362, Flux/5 Core Diameter: 0.70mm Weight: 250 grams/Reel</p>	

# FURUTECH

## FUSE & EXCEPTIONALS



**Destat III**

**19,200.-**

The destat III is incredibly easy to use as it removes dust and static charge from audio/video media in just one 15 seconds treatment. High performance enthusiasts know that static charges on analog and optical media -- LPs, CDs and DVDs – can lead to distracting noise and compromised sound. Simply place your media on the Destat III or hold it over your media of choice and press one button! The powerful fan removes dust while the Destat III's Balanced Ion Flow Generator – releasing just the right balance of positive and negative ions – eliminates static.

Almost every system component benefits from eliminating its static charge. Use the destat III to remove static from the audio/video equipment itself – best to turn them off during treatment – plus power cords, line-level interconnects, speaker cables, and metal record clamps! Some household items may even benefit from static charge removal.

The destat III is small and efficient, powered by four AA batteries and is easily used with one hand. Each dust and static removal takes a mere 15 seconds. And there's a safety circuit preventing shock from the Balanced Ion Flow Generator.

The destat III is third generation model of Furutech's original and well received Destat - just one of Furutech's many treatments for analog and digital playback systems.



**F250**  
**(30pcs./set)**  
**2,880.-/set**

**F114**  
**(10 pcs./set)**  
**970.-/set**

**F118**  
**(10 pcs./set)**  
**970.-/set**

- Furutech F187 & F250 Insulated Female Disconnects Terminals featuring 24k Gold-plated  $\alpha$  (Alpha) phosphor bronze non-magnetic conductor.

F 250 series 0.250(w) X 0.032 "(t) / 6.35(w) X 0.8(t) mm

- Suitable TAB Size: 0.187(w) X 0.032 "(t) / 4.75(w) X 0.8(t) mm.

- Suitable Wire Size:

F 114 --- 2.0 sq. mm max. (16~14 AWG)

F 118 --- 1.25 sq. mm max. (22~18 AWG)

- Insulated Tube: RoHS Compliant PVC (Yellow /Blue / Red).

- Rhodium plated version by request.



**La Source 101**

**17,000.-**

**La Source 101 Long Headshell Leads**

**FEATURES**

- $\alpha$  (Alpha) phosphor bronze rhodium-plated special designed terminal

**SPECIFICATIONS**

- $\alpha$  (Alpha) pure silver conductors, 0.16mm x7pc strand wire (26 AWG)

- Teflon insulation OD: 1.0mm approx.

- Dimensions: Approx 2.5 $\pm$ 0.1mm diameter x 43.5 $\pm$  0.5mm overall length



# FURUTECH

## FUSE & EXCEPTIONALS

**La Grande Épreuve**  
Grand Prix racing's single focus: Testing the absolute limits of technology and performance for that final 10th of a second that makes the difference between victory and defeat. Furutech builds each and every cable in their line the same way; optimized engineering solutions applied to advanced materials and processes, backed by utterly meticulous build quality.

The beautifully finished precision machined nonmagnetic stainless steel base and top modules are girdled by a layer of damping carbon fiber. The bottom surface is covered with 16 concentric cushioning grooves made of an extremely effective Piezo Electric damping material.

**The Piezo Effect and Your Valued LPs**  
Furutech's Pure Transmission Piezo Ceramic Carbon series products--like the Innovations award-winning FI-50 connector series--feature a remarkable "active system" construction. We create a unique material with two "active" materials: Nano-sized ceramic particles and powdered carbon. Only nano-sized ceramic particles effectively couples with carbon powder for the piezo effect to occur. Nylon and fiberglass are incorporated into the construction as well, and the whole forms an extremely effective mechanically and electrically damped material. That's not a misprint; it's electrically damped as well.

Piezoelectric effects are the key. Furutech's employs these nano-sized polycrystalline ferroelectric ceramic particles exhibiting electro-generative properties (mechanical pressure creates an electrical charge) with carbon powder that exhibits thermal-conductive characteristics that interacts with the electrically charged ferro-ceramic particles converting their energy into heat that's conducted away and released from the surface of the material and in doing so making the connection between electrical and mechanical oscillation. The mechanical and electrical damping effects occur while "interconverting" thermal, mechanical, and electrical energy acting as the perfect weighted surface for your LPs.

That's how far Furutech goes to achieve Pure Transmission LP playback, and the Monza.

**Monza LP Stabilizer**  
**28,500.-**

