





# FURUTECH

## Binding Posts

<p><b>For Speaker side</b></p> <p><b>FT-818(R)</b> <b>(2pcs/set)</b> <b>19,800.-</b></p>	<p>Furutech Torque Guard Speaker Binding Posts Model FT-818 (short for amp)</p> <ul style="list-style-type: none"> <li>• Patent-pending Torque Guard construction</li> <li>• Main conductor: <math>\alpha</math> (Alpha) Pure Copper conductor Rhodium or 24k Gold plated</li> <li>• Housing: Carbon fiber, nonmagnetic stainless, eutectic copper alloy</li> <li>• Nylon (red/white) and Polycarbonate (clear) insulation</li> <li>• Connections: Soldered or set-screw</li> <li>• Specified for core diameters up to 4.5mm</li> </ul> <p>Model FT-808 (long for speaker) Dimensions: Housing: 25.0<math>\psi</math> x 30.2mm (L) x 37.4mm overall height Insulation: Polycarbonate (Clear) 19.3<math>\psi</math> x 7.3mm(H), Total overall length: 85.1 mm approx.</p> <p>Model FT-818 (short for amp): Housing: 18.8<math>\psi</math> x 22.7mm (H) overall height Insulation: Polycarbonate (Clear) 19.1<math>\psi</math>± 0.2mm x 7.2mm(H), Total overall length: 52.1 mm approx</p>	
<p><b>For amp side</b></p> <p><b>FT-816(R)</b> <b>(2pcs/set)</b> <b>11,600.-</b></p>	<p>Furutech Carbon Finished Speaker Binding Posts Model FT-816 (short for amp)</p> <ul style="list-style-type: none"> <li>• Main conductor: <math>\alpha</math> (Alpha) Phosphor bronze conductor Rhodium or 24k Gold plated</li> <li>• Housing: Carbon fiber, nonmagnetic stainless, eutectic copper alloy</li> <li>• Nylon (red/white) and Polycarbonate (clear) insulation</li> <li>• Connections: Soldered or set-screw</li> <li>• Specified for core diameters up to 4.5mm</li> </ul> <p>Model FT-816 (short for amp) Housing: 18.8<math>\psi</math> x 22.7mm (H) overall height Insulation: Polycarbonate (Clear) 19.1<math>\psi</math>± 0.2mm x 7.2mm(H), Total overall length: 52.1 mm approx.</p>	
<p><b>FT-809(G)</b> <b>(2pcs/set)</b> <b>7,100.-</b></p> <p><b>FT-809(R)</b> <b>(2pcs/set)</b> <b>8,540.-</b></p>	<p>FT-809 Torque Guard Binding Posts</p> <ul style="list-style-type: none"> <li>• Patent-pending Torque Guard construction</li> <li>• Main conductor: <math>\alpha</math> (Alpha) Pure Copper conductor Rhodium or 24k Gold plated</li> <li>• Housing: Polycarbonate</li> <li>• Nylon (red/white) and Polycarbonate (clear) insulation</li> <li>• Connections: Soldered or Crimp termination</li> <li>• Specified for core diameters up to 4.5mm</li> </ul> <p>Dimensions: Housing unit: 25.0<math>\psi</math> x 30. mm (L) x 38.9mm overall height Insulation: Polycarbonate (Clear) 19.3<math>\psi</math> x 7.3mm(H), Total overall length: 79.0 mm approx.</p>	
<p><b>FP-803(G)</b> <b>(2pcs/set)</b> <b>4,750.-</b></p> <p><b>FP-803(R)</b> <b>(2pcs/set)</b> <b>5,670.-</b></p>	<p>Furutech High Performance Binding Posts</p> <ul style="list-style-type: none"> <li>• Main conductor: <math>\alpha</math> (Alpha) Phosphor bronze conductor 24k Gold plated</li> <li>• Housing: Fog black finished eutectic copper alloy</li> <li>• Nylon (red/white) and Polycarbonate (clear) insulation</li> <li>• Connections: Soldered or s</li> </ul>	

# FURUTECH

## Binding Posts



**FT-807(G)**  
(2pcs/set)  
5,000.-

**FT-807(R)**  
(2pcs/set)  
5,770.-

- Main conductor: Rhodium or 24k gold-plated  $\alpha$  (Alpha) Pure copper conductor
- Housing: Matte black finished nylon and fiberglass with piezo ceramic resin.
- Nylon (red/black) and Polycarbonate (Transparent hue) fully insulated
- Connections: Soldered or screw termination
- Specified for core diameters up to 4.5mm

Dimensions: Housing: 20.4 X 18.0 $\phi$  x 28.0mm (H) overall height  
Insulation: Polycarbonate (Transparent black ) 20.0 $\phi$ ± 0.2mm x 15.6mm(H),  
Total overall length: 62.76 mm approx.



**FT-865(R)**  
(2pcs/set)  
5,400.-

- Patent-pending One piece wound-wire construction
- Main conductor: Rhodium  $\alpha$  (Alpha)-OCC wound-wire conductor
- Housing: Eutectic copper alloy
- POM plastic injected terminal pole
- Nylon (red/white) and Polycarbonate insulation
- Connections: Disconnect connector termination
- Specified for core diameters up to 4.5mm

Furutech recommends terminating the FT-865 binding posts with Furutech FT-210 Pure Copper disconnect terminals



**FT-866(R)**  
(2pcs/set)  
10,000.-

- Patent-pending One piece wound-wire construction
- Main conductor: Rhodium  $\alpha$  (Alpha)-OCC wound-wire conductor
- Housing: Carbon fiber and nonmagnetic stainless
- POM plastic injected terminal pole
- Nylon (red/white) and Polycarbonate insulation
- Connections: Disconnect connector termination
- Specified for core diameters up to 4.5mm

Furutech recommends terminating the FT-866 binding posts with Furutech FT-210 Pure Copper disconnect terminals



**FT-867(R)**  
(2pcs/set)  
4,850.-

- Patent-pending One piece wound-wire construction
- Main conductor: Rhodium  $\alpha$  (Alpha)-OCC wound-wire conductor
- Housing: Nylon/fiberglass with piezo ceramic and carbon damping material
- POM plastic injected terminal pole
- Nylon (red/white) and Polycarbonate insulation
- Connections: Disconnect connector termination
- Specified for core diameters up to 4.5mm

Furutech recommends terminating the FT-867 binding posts with Furutech FT-210 Pure Copper disconnect terminals

