




FURUTECH

Finished Digital Cable

<p>HDMI-N1-4</p> <p>1.2 M (9,550.-) 2.5 M (15,300.-) 5.0 M (25,700.-) 8.0 M (33,400.-)</p>	<ul style="list-style-type: none"> • Main conductors: Nonmagnetic α (Alpha) silver-plated μ-OFC for minimal transmission loss • HDMI connector: Nonmagnetic 24k gold-plated α (Alpha) conductor with 24k gold-plated nonmagnetic copper alloy body • Jacket: RoHS-compliant flexible PVC • Triple shielding assures superior noise isolation • Available in 1.2m/2.5m/5m/8m/10m/12m/15m/20m lengths 	
<p>HDMI – xv 1.3</p> <p>1 M (19,300.-) 2 M (24,200.-) 3 M (28,900.-) 5 M (38,600.-)</p>	<p>HDMI Digital Cable – xv1.3 (High-Definition Multimedia Interface Cable)</p> <p>Successfully completed ATC Compliance testing at the HDMI Authorized Testing Center---Silicon Image (1080P / 1.3b Ver. Cat.2 / 10.2 Gbps / 16 bit / 60Hz max.). (1080P / 1.3b ver. / Cat.2 / 13.4 Gbps / 12 bit / 120Hz max.) 1m, 2m, 3m, 5m only</p> <p>Main Conductor: α(Alpha) conductor (24 AWG Silver plated μ-OFC solid core wire) for ultra low transmission loss.</p> <p>HDMI Connector constructed of Pearl Chrome finished Aluminum Alloy with non-magnetic 24K Gold Plated α (Alpha) contacts</p> <p>Cable: UL Specified Pb free Fire-retardant PVC Sheath and 5 layer shielding around conductors for superior noise isolation.</p> <p>Production Lengths: 1M/2M/3M/5M/8M/10M/12M/15M/20M.</p> <p>α(Alpha) conductor : Silver plated μ-OFC conductor wire strands treated with the α(Alpha) process.</p>	
<p>GT2 USB</p> <p>GT2 0.6 m. 5,500.- GT2 1.2 m. 6,550.- GT2 1.8 m. 7,580.- GT2 3.6 m. 10,700.- GT2 5.0 m. 13,100.-</p>	<p>Furutech GT2 USB 2.0 Cables</p> <p>Features</p> <ul style="list-style-type: none"> • Main conductor: Silver-plated α (Alpha) OCC Conductors • Main Insulation: Special-grade high-density polyethylene • 3-layer shield construction for improved noise insulation • Connectors: Furutech-engineered 24k gold-plated USB series Connectors • The best damping and insulation materials for improved frequency extension and tonal balance <p>• Cable Types</p> <ul style="list-style-type: none"> o GT2 USB-A (Type A-A) / USB-B (Type A-B) / USB-mini B (Type A-mini B) <p>• Cable Lengths</p> <ul style="list-style-type: none"> o 0.6m (2ft) / 1.2m (4ft) / 1.8m (6ft) / 3.6m (12ft) / 5.0m (16.5ft) o 7.0m (23ft) and 10.0m (33ft) by request 	

FURUTECH

Finished Digital Cable

<p>LAN-7</p> <p>LAN-10G 0.6m. 5,750.-</p> <p>LAN-10G 1.2m. 6,950.-</p> <p>LAN-10G 1.8m. 8,150.-</p> <p>LAN-10G 2.5m. 9,280.-</p> <p>LAN-10G 3.6m. 11,380.-</p> <p>LAN-10G 5.0m. 13,900.-</p>	<p>LAN-7 Ethernet Cable Category 7 (STP/ Class F)</p> <ul style="list-style-type: none"> • The LAN-7 is a beautifully engineered and built Category 7 STP twisted pair cable for Ethernet and other high-speed signal transfer. • Category 7 is backward compatible with Categories 5e and 6. It also features improved specifications for crosstalk and system noise than Category 6a with added shielding for each individual wire pair and the cable as a whole. Besides the additional shielding, the LAN-7 features twisted pairs with the number of twists per unit length increasing RF shielding and protecting from crosstalk. • Category 7 cable allows 10 Gigabit Ethernet over 100m and frequencies of up to 600 MHz. • Main conductor wire: 24 AWG Silver plated α (Alpha) OCC conductor for minimal transmission loss. • RJ45(8P8C) Connector: α (Alpha) non-magnetic 24k Gold-plated conductor with 24k Gold-plated copper alloy body that has minimal magnetic properties. • 3 Layered Shielding with superior noise isolation aluminum foil and copper braiding. • The best damping and insulation materials for improved frequency extension and tonal balance • Jacket: 84A UL/CL2 approved flammability grade; RoHS Compliant Flexible PVC (Black). OD: 7.0\pm0.15mm approx. • Production Lengths: 0.6M/1.2M/1.8M/2.5M/3.6M/5M other sizes by request. 	
<p>F-1 Adaptor</p> <p>2,650.-</p>	<p>HDMI female to DVI-D male Adaptor</p> <p>Gold Plated α(Alpha)conductor</p>	

FURUTECH

Finished Digital Cable

GT2 Pro USB

- 0.3 m. **8,900.-**
- 0.6 m. **9,900.-**
- 1.2 m. **11,900.-**
- 1.8 m. **13,900.-**

Following on from the success of the Furutech GT2 USB cable Furutech now introduces the higher specified GT2Pro 2.0 USB cable. The cable is formed around special α (Alpha) OCC silver copper alloy conductors with superior high-density polyethylene insulation/dielectric. As illustrated below the GT2Pro features three-layer shielding and specially engineered 24k gold-plated USB 2.0 connectors with a special 24k gold-plated copper alloy EMI shield incorporated into the connector. The cable wrap includes damping and insulating materials keeping mechanical ringing from affecting the sound. A carefully engineered clamp improves grip and keeps both mechanical and electrical distortion at bay.

The result: Clear and open highs, elegant midrange textures, powerful but in-control bass, and an enhanced sense of the sheer palpability of the music you'll enjoy. The GT2Pro series creates real musical experience from the data stored on your computer.

