

# FURUTECH

## IEC Connector

<p><b>FI-33(R)</b> <b>5,400.-/pcs.</b></p> <p><b>FI-33(G)</b> <b>5,200.-/pcs.</b></p>	<p>High End Performance 20A IEC Inlet</p> <ul style="list-style-type: none"> <li>• Pure copper <math>\alpha</math> (Alpha) Conductor</li> <li>• Material: Nylon/fiberglass</li> <li>• Specified for wire diameters of 4mm (set screw)</li> <li>• Dimensions: 60.4mm (W) x 30.4mm (D) x 38.7mm (H)</li> <li>• Rated: 20A/125V and 16A/250V</li> </ul>	
<p><b>FI-09(R)</b> <b>4,800.-/pcs.</b></p> <p><b>FI-09(G)</b> <b>4,150.-/pcs.</b></p>	<p>High End Performance IEC Inlet</p> <p>Pure copper <math>\alpha</math> (Alpha) Conductor</p> <ul style="list-style-type: none"> <li>• Materials: Nylon/fiberglass</li> <li>• Specifications: Accommodates wire diameters to 4mm (set-screw)</li> <li>• Dimensions: 60 (W) x 30mm (D) x 36.2mm (H)</li> <li>• Body length 40.0mm x 44mm diameter x 80mm overall length</li> <li>• Rated: 15A/250V</li> </ul>	 <p>FI-09 (R)</p>
<p><b>AC-INLET (R)</b> <b>1,000.-/pcs.</b></p> <p><b>AC-INLET(G)</b> <b>700.-/pcs</b></p>	<p>High Performance IEC Inlet</p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) copper alloy conductor</li> <li>• PBT and fiberglass housing</li> <li>• Dimensions: 44.0mm (W) x 28.6mm (D) x 33.0mm (H)</li> <li>• Rating: 10A/250V</li> <li>• Standard : IEC 320-1 C14</li> <li>• Approvals : UL/CSA/VDE/DEMKO/SEMKO/NEMKO/FIMKO</li> </ul>	
<p><b>FI-03(R)</b> <b>1,350.-/pcs.</b></p> <p><b>FI-03(G)</b> <b>1,200.-/pcs.</b></p>	<p>High Performance IEC Inlet</p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) Eutectic (low temperature) cast copper alloy Conductor</li> <li>• PBT and fiberglass housing</li> <li>• Connections: Soldered</li> <li>• Dimensions: 50.9mm (W) x 24.1mm (D) x 28.8 (H)</li> <li>• Rated: 15A/125V 10A/250V</li> </ul>	
<p><b>FI-06(R)</b> <b>1,600.-/pcs.</b></p> <p><b>FI-06(G)</b> <b>1,550.-/pcs.</b></p>	<p>FI-06(G) &amp; FI-06(R)</p> <p>Gold or Rhodium plated <math>\alpha</math> (Alpha) Conductors milled from solid Pure Copper</p> <p>Rated: 15A/250V</p> <ul style="list-style-type: none"> <li>• Materials: Nylon/fiberglass</li> <li>• Specifications: Accommodates wire diameters up to 3.5mm (set-screw)</li> <li>• Dimensions: 50.5 (W) x 23.9mm (D) x 33.5mm (H) <math>\pm 0.1</math>mm</li> </ul>	

# FURUTECH

## IEC Connector

 <p><b>FI-06 NCF(R)</b> 2,250-/pcs.</p>	<p><b>Furutech's Ultimate IEC Inlet Series</b></p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) Pure-Copper Rhodium-plated Conductor</li> <li>• Materials: Nylon/fiberglass with special "NCF" anti-resonance damping material - nano-sized crystalline, piezo ceramic particles and carbon powder</li> <li>• Specifications: Accommodates wire diameters up to 3.5mm (set-screw)</li> <li>• Dimensions: 50.5 (W) x 23.9mm (D) x 33.5mm (H) <math>\pm</math>0.1mm</li> <li>• Rated: 15A/250V</li> </ul>	
 <p><b>FI-09 NCF</b> 5,950-/pcs.</p>	<p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) Pure-Copper Rhodium-plated Conductor</li> <li>• Materials: Nylon/fiberglass with special "NCF" anti-resonance damping material - nano-sized crystalline, piezo ceramic particles and carbon powder</li> <li>• Specifications: Accommodates wire diameters up to 4.0mm (set-screw)</li> <li>• Dimensions: 60.5 (W) x 30.2mm (D) x 36.2mm (H) <math>\pm</math>0.1mm</li> <li>• Type: 2-pole+earth, Rated: 15A/250V</li> </ul>	
 <p><b>FI-33 NCF</b> 6,500-/pcs.</p>	<p><b>SPECIFICATIONS</b></p> <ul style="list-style-type: none"> <li>• <math>\alpha</math> (Alpha) Pure-Copper Rhodium-plated Conductor</li> <li>• Materials: Nylon/fiberglass with special "NCF" anti-resonance damping material - nano-sized crystalline, piezo ceramic particles and carbon powder</li> <li>• Specifications: Accommodates wire diameters up to 4.0mm (set-screw)</li> <li>• Dimensions: 60.5 (W) x 30.4mm (D) x 38.7mm (H) <math>\pm</math>0.1mm</li> <li>• Type: 2-pole+earth, Rated: 16A/250V // 20A/125V</li> </ul>	