

FURUTECH

Receptacle & Cover



GTX-D NCF(R)

14,500.-

Furutech's Ultimate AC Receptacle Series

- Rhodium-plated α (Alpha) Pure Copper Conductor (0.8mm)
- Nonmagnetic stainless conductor spring system
- Body material: Nylon/fiberglass with anti-resonance nano-sized crystalline, piezo ceramic particles and carbon.
- Cover material: Polycarbonate with a special anti-resonance nano-sized crystalline material "NCF"
- Parts set with nonmagnetic 2.0mm-thick stainless brace plate
- Specified for wire diameters of 4mm (set screw)
- Dimensions: 104.0 mm (L) x 47.2 mm (W) x 28.0 mm (H)
- Total attention to detail and build quality extends right down to a specially designed patent-pending conductor pressure plate that increases contact area
- Furutech spade terminal FP-205 recommended for 10 AWG wire

NCF



GTX-D(R)

12,300.-

GTX-D(G)

10,700.-

Furutech's Top-Tier GTX Receptacles

- Rhodium or gold-plated α (Alpha) Pure Copper Conductor (0.8mm)
- Nonmagnetic stainless conductor spring system
- Body material: Nylon/fiberglass with piezo ceramic and carbon damping material
- Cover material: Polycarbonate
- Parts set with nonmagnetic 2.0mm-thick stainless brace plate
- Specified for wire diameters of 4mm (set screw)
- Dimensions: 104.0 mm (L) x 47.2 mm (W) x 28.0 mm (H)
- Total attention to detail and build quality extends right down to a specially designed patent-pending conductor pressure plate (see below) that increases contact area
- Furutech spade terminal FP-209 recommended for 10 AWG wire



FPX-(R)

6,250.-

FPX-(G)

5,200.-

FPX-(Cu)

3,700.-


High Performance Duplex Receptacles

All non-magnetic α (Alpha) Phosphor bronze Conductor
All models c(UL) approved
Unique pin insert construction ensures increased contact areas, stable transmission and the tightest contacts in the Audio industry and they won't scratch or mark the plating on male AC connectors!
Accommodates cable diameters from 10 AWG to 24 AWG.
Dimensions: 104.2mm×33.5mm (L×W), 28.2mm thick.
Materials: Main body: Nylon and Fiber Glass
Cover: White polycarbonate for FPX- (R) and (G), Black for FPX- (Cu)
Connections: Set-screw
Non-magnetic Rhodium, 24k Gold or Non plated Phosphor Bronze conductor (t: 0.8 mm)



FURUTECH

Receptacle & Cover

<p>GTX-S NCF(R)</p> <p>12,500.-</p>	<p>GTX-S NCF(R): 20A 125V Furutech's Top-Tier GTX –S NCF Receptacles SPECIFICATIONS *Rhodium-plated α (Alpha) Pure Copper Conductor (0.8mm) Nonmagnetic stainless conductor spring system *Body material: Nylon/fiberglass with a special anti-resonance nano-sized crystalline, piezo ceramic particles and carbon damping material *Cover material: Polycarbonate with a special anti-resonance nano-sized crystalline material "NCF" *Parts set with nonmagnetic 2.0mm-thick stainless brace plate *Specified for wire diameters of 4mm (set screw) *Dimensions: 104.0 mm (L) x 47.2 mm (W) x 28.0 mm (H) Total attention to detail and build quality extends right down to a specially designed patent-pending conductor pressure plate (see below) that increases contact area *Furutech spade terminal FP-209 recommended for 10 AWG wire</p>	

FURUTECH

Receptacle & Cover

<p>GTX Wall Plate</p> <p>8,600.-</p>	<p>High Performance Wall Plate for Duplex /Single Outlets</p> <ul style="list-style-type: none"> • Beautifully crafted special grade aluminum CNC processed chassis effectively shields against RFI (Radio Frequency Interference). • Material thickness: chassis plate 13.0mm • Finished with an extremely effective nonresonant coating. • Includes Special Teflon damping foil and SUS Receptacle fixed screw 4 pcs (M3) and SUS Plate fixed screw 2 pcs (50mm overall length). • Suitable for use with GTX-D or GTX-S receptacle and 104-D or 104-S carbon fiber finished cover. • Dimensions: 135.0mm (L) x 86.0mm (W) x 13.0mm(H) - 0/+0.3mm 								
<p>Outlet cover 106-D NCF</p> <p>8,500.-</p> <p>Outlet cover 106-S NCF</p> <p>8,500.-</p>	<p>106-D NCF High End Performance NCF Damper Outlet Cover</p> <p>SPECIFICATIONS Features: Formed from a hybrid NCF carbon fibre sheet over a non-magnetic stainless-steel base plate with a special NCF coating material finish - for the most effective damping faceplate available. New Improved Outlet Cover for GTX-D NCF / GTX-D / FPX duplex receptacle designs. Stainless fixed screw size : M4 X 12mm (L) , Cover overall size : 72.2 x 117 x 5.5 mm±0.2mm Net Weight: 74g approx. (tolerance scope: ± 2g)</p> <p>Multilayer Structure description</p> <table border="1" data-bbox="416 1093 703 1218"> <tr><td>NCF Coating Material (Matte finish)</td></tr> <tr><td>Clear Hard Coat Layer</td></tr> <tr><td>Hybrid NCF 3K Carbon Fiber</td></tr> <tr><td>Non-Magnetic Stainless-steel Base Plate</td></tr> <tr><td>NCF Carbon Fiber</td></tr> <tr><td>Clear Hard Coat Layer</td></tr> <tr><td>NCF Coating Material (Matte finish)</td></tr> </table> 	NCF Coating Material (Matte finish)	Clear Hard Coat Layer	Hybrid NCF 3K Carbon Fiber	Non-Magnetic Stainless-steel Base Plate	NCF Carbon Fiber	Clear Hard Coat Layer	NCF Coating Material (Matte finish)	
NCF Coating Material (Matte finish)									
Clear Hard Coat Layer									
Hybrid NCF 3K Carbon Fiber									
Non-Magnetic Stainless-steel Base Plate									
NCF Carbon Fiber									
Clear Hard Coat Layer									
NCF Coating Material (Matte finish)									
<p>Outlet cover 102-D</p> <p>2,000.-</p> <p>Outlet cover 102-S</p> <p>2,000.-</p>	<p>New and greatly improved Pure Transmission 102-D Duplex Receptacle Cover Plate</p> <p>102 series: Stainless Fixed Screw/Size : M4 X 12mm(L) Stainless Cover /Size : 71X116 mm(t : 1.2mm) With "FO-Q" vibration damping material c(UL) Approved</p>								